




Ex-d EXIOS Cable Glands  
 Ex-d Nickel Plated Brass & Stainless Steel Glands  
 Ex-e Nylon Glands  
 Ex-e Multi-Hole & Romex Glands  
 Ex-e Nickel Plated Brass & Stainless Steel Glands  
 Ex-e EMI / RFI Nickel Plated Brass Glands  
 Ex-e / Ex-d Accessories  
 Technical Information

For Non-Armored Cable

Fiber Reinforced Nylon & Nickel Plated Brass, Cable Glands with Multi-Hole Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68

Part Numbers			Thread Type & Size	Dimensions in Inches (mm)				
-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)		No. of Holes	Diameter of Holes		Part Numbers of Inserts only	
Black	Blue	Nickel Plated Brass	mm		Inches			
			3/8" NPT Page 59 for Thread Specs	4	1.4	.06	1.089.0900.19	
CD09N1-BXA	CD09N1-BXI	CD09N1-MX		2	3.0	.12	1.089.0901.19	
CD09N2-BXA	CD09N2-BXI	CD09N2-MX		5	1.6	.06	1.089.0902.19	
CD09N3-BXA	CD09N3-BXI	CD09N3-MX		2	1.7	.07	1.089.0903.19	
CD09N4-BXA	CD09N4-BXI	CD09N4-MX		10	1.4	.06	1.089.0904.19	
CD09N5-BXA	CD09N5-BXI	CD09N5-MX		6	1.4	.06	1.089.0905.19	
CD09N6-BXA	CD09N6-BXI	CD09N6-MX		3	1.7	.07	1.089.0906.19	
CD09N7-BXA	CD09N7-BXI	CD09N7-MX		4	1.7	.07	1.089.0907.19	
CD09N8-BXA	CD09N8-BXI	CD09N8-MX		4	2.3	.09	1.089.0908.19	
CD09N9-BXA	CD09N9-BXI	CD09N9-MX		Solid Insert			1.089.0999.19	
CD09NP-BXA	CD09NP-BXI	CD09NP-MX						
CD13N1-BXA	CD13N1-BXI	CD13N1-MX		1/2" NPT	3	2.0	.08	1.089.1300.19
CD13N2-BXA	CD13N2-BXI	CD13N2-MX			6	3.0	.12	1.089.1301.19
CD13N3-BXA	CD13N3-BXI	CD13N3-MX	3		4.0	.16	1.089.1302.19	
CD13N4-BXA	CD13N4-BXI	CD13N4-MX	2		5.0	.20	1.089.1303.19	
CD13N5-BXA	CD13N5-BXI	CD13N5-MX	3		3.0	.12	1.089.1304.19	
CD13N6-BXA	CD13N6-BXI	CD13N6-MX	2		5.2	.20	1.089.1305.19	
CD13N7-BXA	CD13N7-BXI	CD13N7-MX	2		3.8	.15	1.089.1306.19	
CD13N8-BXA	CD13N8-BXI	CD13N8-MX	2		4.2	.17	1.089.1307.19	
CD13N9-BXA	CD13N9-BXI	CD13N9-MX	2		2.5	.10	1.089.1308.19	
CD13NP-BXA	CD13NP-BXI	CD13NP-MX	Solid Insert			1.089.1399.19		
CD16N0-BXA	CD16N0-BXI	CD16N0-MX	1/2"-E NPT	6	3.8	.15	1.089.1609.19	
CD16N1-BXA	CD16N1-BXI	CD16N1-MX		3	3.0	.12	1.089.1600.19	
CD16N2-BXA	CD16N2-BXI	CD16N2-MX		3	4.0	.16	1.089.1601.19	
CD16N3-BXA	CD16N3-BXI	CD16N3-MX		4	4.0	.16	1.089.1602.19	
CD16N4-BXA	CD16N4-BXI	CD16N4-MX		5	4.0	.16	1.089.1603.19	
CD16N5-BXA	CD16N5-BXI	CD16N5-MX		6	4.0	.16	1.089.1604.19	
CD16N6-BXA	CD16N6-BXI	CD16N6-MX		2	6.0	.24	1.089.1605.19	
CD16N7-BXA	CD16N7-BXI	CD16N7-MX		3	5.6	.22	1.089.1606.19	
CD16N8-BXA	CD16N8-BXI	CD16N8-MX		6	3.0	.12	1.089.1607.19	
CD16NP-BXA	CD16NP-BXI	CD16NP-MX	Solid Insert			1.089.1699.19		

\* Note: IECEx approval apply only to Nickel Plated Brass Multi-Hole  
 \*\*Note: UL f1 (746C) rating applies to Black Nylon Fittings only.

For Specifications and Dimensions for Black & Gray Nylon (page 22) or Nickel Plated Brass (page 35) where the appropriate Fittings are listed.



For Non-Armored Cable

Fiber Reinforced Nylon & Nickel Plated Brass, Cable Glands with Multi-Hole Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68

Part Numbers			Thread Type & Size	Dimensions in Inches (mm)			Part Numbers of Inserts only
-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)		No. of Holes	Diameter of Holes		
Black	Blue	Nickel Plated Brass	Page 59 for Thread Specs		mm	Inches	
				3/4" NPT	4	6.0	.24
CD21N1-BXA	CD21N1-BXI	CD21N1-MX	3		7.0	.28	1.089.2101.19
CD21N2-BXA	CD21N2-BXI	CD21N2-MX	2		8.0	.31	1.089.2102.19
CD21N3-BXA	CD21N3-BXI	CD21N3-MX	4		5.0	.20	1.089.2103.19
CD21N4-BXA	CD21N4-BXI	CD21N4-MX	1		8.0	.31	1.089.2104.19
CD21N5-BXA	CD21N5-BXI	CD21N5-MX	4		5.2	.20	1.089.2105.19
CD21N6-BXA	CD21N6-BXI	CD21N6-MX	3		5.2	.20	1.089.2106.19
CD21N7-BXA	CD21N7-BXI	CD21N7-MX	4/1		5.2/3.7	.20/.15	1.089.2107.19
CD21N8-BXA	CD21N8-BXI	CD21N8-MX	2		7.4	.29	1.089.2108.19
CD21N9-BXA	CD21N9-BXI	CD21N9-MX	Solid Insert			1.089.2199.19	
CD21NP-BXA	CD21NP-BXI	CD21NP-MX					
CD29N1-BXA	CD29N1-BXI	CD29N1-MX	1" NPT		6	6.5	.26
CD29N2-BXA	CD29N2-BXI	CD29N2-MX		4	9.0	.35	1.089.2901.19
CD29N3-BXA	CD29N3-BXI	CD29N3-MX		4	9.5	.37	1.089.2902.19
CD29NP-BXA	CD29NP-BXI	CD29NP-MX		Solid Insert			1.089.2999.19
CD29L1-BXA	CD29L1-BXI	-	1-1/4" NPT	6	6.5	.26	1.089.2900.19
CD29L2-BXA	CD29L2-BXI	-		4	9.0	.35	1.089.2901.19
CD29L3-BXA	CD29L3-BXI	-		4	9.5	.37	1.089.2902.19
CD29LP-BXA	CD29LP-BXI	-		Solid Insert			1.089.2999.19
CD36N1-BXA	CD36N1-BXI	-	1-1/2" NPT	5	9.0	.35	1.089.3600.19
CD36N2-BXA	CD36N2-BXI	-		7	9.0	.35	1.089.3601.19
CD36N3-BXA	CD36N3-BXI	-		6	8.0	.31	1.089.3602.19
CD36N4-BXA	CD36N4-BXI	-		2	15.0	.59	1.089.3603.19
CD36NP-BXA	CD36NP-BXI	-		Solid Insert			1.089.3699.19

\* Note: IECEx approval apply only to Nickel Plated Brass Multi-Hole  
\*\*Note: UL f1 (746C) rating applies to Black Nylon Fittings only.

\*\*\*Note: InMetro only applies to all Nylon Cable Glands.

For Specifications and Dimensions for Black & Gray Nylon (page 22) or Nickel Plated Brass (page 35) where the appropriate Fittings are listed.

