

## Fiber Reinforced Nylon Strain Relief Fitting (BXA)

This non-metallic solution for non-armored cables is designed for applications in electrical equipment and potentially explosive atmospheres.

### Now Available For Low Voltage Applications (BXI)

- **Material:** Black Fiber Reinforced Nylon
- **Protection Rating:** IP68 (10 bar)
- **High Impact Resistance:** 7 Joule
- **Low Smoke:** Halogen-free (V0)
- **Temperature Range:** -4°F to 185°F (-20°C to 85°C)
- **Zones:** 1, 2, 20, 21, 22
- **Sizes:** M12 - M63, NPT 3/8" - NPT 1 1/2"
- **Approvals:** CSA, ATEX, IECEx
- **ATEX Certificate:** BVS 14 ATEX E 025 X
- **IECEX Certificate of Conformity:** IECEX BVS 14.0020X
- **CSA Certificate:** 70010389

**DIN EN  
 60079-0: 2012**



#### Meets Latest Standards

EN 60079-0: 2012	IEC 60079-7: 2015
EN 60079-31: 2014	

#### Markings

II 2G Ex eb IIC Gb  
 II 1D Ex ta IIIC Da

#### CSA Approvals

cUS Class 1 & Div 2  
 cUS Class 2 & Div 1  
 cUS Zone 1

