




For Non-Armored Cable

Nylon, Cable Glands with Romex® Inserts, Hazardous Duty Locations, Black/Gray, V0, UL 94, NEMA 6, IP 68

Part Numbers		Slot Size	Thread Type & Size	Dimensions in Inches (mm)			
-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)			A	B	C	F ₁ /F
Black  (Standard)	Gray  (Standard)	Inches (mm) H x W	Page 55 for Thread Specs	Clearance Hole +.01" (+.25 mm)	Body Length (Dome)	Thread Length (Standard)	Wrench Flats
CD16NS-E5	CD16NS-E6	.28 x .47 (7 x 12)	1/2"-E NPT	.83 (21.1)	1.10 (28)	.51 (13)	1.06 (27)
CD16NS-E1	CD16NS-E2	.24 x .55 (6 x 14)					
CD21NS-E1	CD21NS-E2	.24 x .55 (6 x 14)					
CD29NS-E1	CD29NS-E2	.31 x .87 (8 x 22)	1" NPT	1.35 (34.3)	1.53 (39)	.75 (19)	1.65 (42)
CD29LS-E1	CD29LS-E2	1.26 x .87 (8 x 22)	1-1/4" NPT	1.65 (41.9)	1.53 (39)	.63 (16)	1.65 / 1.81 (42 / 46)
CD36NS-E1	CD36NS-E2	.39 x 1.12 (10 x 28.5)	1-1/2" NPT	1.92 (48.7)	2.09 (53)	.26 (6.5)	.55 (14)
CD36NS-E3	CD36NS-E4	.22 x 1.14 (5.5 x 29)					
CD36NS-E5	CD36NS-E6	.47 x 1.20 (12 x 30.5)					
CD36NS-E7	CD36NS-E8	.30 x 1.22 (7.5 x 31)					
CD22MS-E5	CD22MS-E6	.28 x .47 (7 x 12)	M20 x 1.5	.79 (20)	1.10 (28)	.35 (9)	1.06 (27)
CD22MS-E1	CD22MS-E2	.24 x .55 (6 x 14)	M25 x 1.5	.98 (25)	1.22 (31)	.43 (11)	1.29 (33)
CD25MS-E1	CD25MS-E2	.24 x .55 (6 x 14)					
CD25MS-E3	CD25MS-E4	.28 x .55 (7 x 14)					
CD32MS-E1	CD32MS-E2	.31 x .87 (8 x 22)	M32 x 1.5	1.26 (32)	1.53 (39)	.43 (11)	1.65 (42)
CD40MS-E1	CD40MS-E2	.39 x 1.12 (10 x 28.5)	M40 x 1.5	1.57 (40)	1.89 (48)	.51 (13)	2.09 (53)
CD40MS-E3	CD40MS-E4	.20 x 1.14 (5.5 x 29)					
CD40MS-E5	CD40MS-E6	.47 x 1.20 (12 x 30.5)					
CD40MS-E7	CD40MS-E8	.30 x 1.22 (7.5 x 31)					
CD50MS-E1	CD50MS-E2	.45 x 1.31 (11.5 x 33.5)	M50 x 1.5	1.97 (50)	1.93 (49)	.51 (13)	2.36 (60)
CD16AS-E5	CD16AS-E6	.28 x .47 (7 x 12)	PG 16	.89 (22.5)	1.10 (28)	.39 (10)	1.06 (27)
CD16AS-E1	CD16AS-E2	.24 x .55 (6 x 14)					
CD21AS-E1	CD21AS-E2	.24 x .55 (6 x 14)	PG 21	1.12 (28.4)	1.22 (31)	.43 (11)	1.29 (33)
CD21AS-E3	CD21AS-E4	.28 x .55 (7 x 14)					
CD29AS-E1	CD29AS-E2	.31 x .87 (8 x 22)	PG 29	1.47 (37.3)	1.53 (39)	.43 (11)	1.65 (42)
CD36AS-E1	CD36AS-E2	.39 x 1.12 (10 x 28.5)	PG 36	1.85 (47)	1.89 (48)	.51 (13)	2.09 (53)
CD36AS-E3	CD36AS-E4	.20 x 1.14 (5.5 x 29)					
CD36AS-E5	CD36AS-E6	.47 x 1.20 (12 x 30.5)					
CD36AS-E7	CD36AS-E8	.30 x 1.22 (7.5 x 31)					
CD42AS-E1	CD42AS-E2	.45 x 1.31 (11.5 x 33.5)	PG 42	2.13 (54.1)	1.93 (49)	.51 (13)	2.36 (60)

*Note: UL f1 (746C) rating applies to Black Nylon Fittings only.

ROMEX® is a federally registered trademark of Southwire Company.



Cable Glands with Inserts for Flat Cables

These form seals are also available with Cable Glands made of other materials. (Nickel Plated Brass, Stainless Steel, etc.)

* Additional UL Information

- Our FLAKA (for Romex® style cable) HSK-K-Ex PG 16 & 1/2"-Enlarged are UL listed. UL file # E168975.
- To meet UL, only Romex® style cable (flat top and bottom) can be used with this style Cable Glands (No Zip Cable, No Ribbon cable, etc.)
- Hummel Multi-hole solutions meet IP68 / 10 BAR as long as the conductor outer diameter is not smaller than 20% of the hole diameter, or max 1 mm (.04") each. We recommend a customer performing his/her own testing.



Ex-d EXIOS
Ex-d Nickel Plated Brass & Stainless Steel Glands
Nylon Glands
Ex-e
Ex-e Multi-Hole & Romex Glands
Ex-e Nickel Plated Brass & Stainless Steel Glands
Ex-e EMI / RFI Nickel Plated Brass Glands
Ex-e Conduit & Fitting Systems
Ex-e / Ex-d Accessories
Technical Information