


Ex-d EXIOS Cable Glands
 Ex-d Nickel Plated Brass & Stainless Steel Glands
 Ex-e Nylon Glands
 Ex-e Multi-Hole & Romex Glands
 Ex-e Nickel Plated Brass & Stainless Steel Glands
 Ex-e EMI / RFI Nickel Plated Brass Glands
 Ex-e Conduit & Fitting Systems
 Ex-e / Ex-d Accessories
 Technical Information

Ex-e Nickel Plated Brass - Romex® Cable Glands Fittings - NPT / Metric & PG Threads



For Non-Armored Cable

Nickel Plated Brass, Cable Glands with Romex® Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68

Part Numbers	Slot Size	Thread Type & Size	Dimensions in Inches (mm)			
			A	B	C	F ₁ /F
-4°F to 203°F (-20°C to 95°C)						
Nickel Plated Brass  (Standard)	Inches (mm) H x W	Page 55 for Thread Specs	Clearance Hole +.01" (+.25 mm)	Body Length (Dome)	Thread Length (Standard)	Wrench Flats
CD21NS-EB1	.24 x .55 (6 x 14)	3/4" NPT	1.05 (26.7)	.98 (25)	.51 (13)	1.18 (30)
CD21NS-EB2	.28 x .55 (7 x 14)					
CD29NS-EB1	.31 x .87 (8 x 22)					
CD22MS-EB2	.28 x .47 (7 x 12)	M20 x 1.5	.79 (20)	.94 (24)	.24 (6)	.94 (24)
CD22MS-EB1	.24 x .55 (6 x 14)					
CD25MS-EB1	.24 x .55 (6 x 14)	M25 x 1.5	.98 (25)	1.02 (26)	.28 (7)	1.18 (30)
CD25MS-EB2	.28 x .55 (7 x 14)					
CD32MS-EB1	.31 x .87 (8 x 22)	M32 x 1.5	1.26 (32)	1.22 (31)	.31 (8)	1.57 (40)
CD40MS-EB1	.39 x 1.12 (10 x 28.5)	M40 x 1.5	1.57 (40)	1.46 (37)	.31 (8)	1.97 (50)
CD40MS-EB2	.20 x 1.14 (5.5 x 29)					
CD40MS-EB3	.47 x 1.18 (12 x 30)					
CD40MS-EB4	.29 x 1.22 (7.5 x 31)					
CD50MS-EB1	.45 x 1.31 (11.5 x 33.5)	M50 x 1.5	1.97 (50)	1.46 (37)	.35 (9)	2.24 (57)
CD63MS-EB1	.47 x 1.50 (12 x 38)	M63 x 1.5	2.48 (63)	1.49 (38)	.39 (10)	2.52 (64) / 2.68 (68)
CD16AS-EB1	.24 x .55 (6 x 14)	PG 16	.89 (22.5)	.91 (23)	.26 (6.5)	.94 (24)
CD16AS-EB2	.28 x .47 (7 x 12)					
CD21AS-EB1	.24 x .55 (6 x 14)	PG 21	1.12 (28.4)	.94 (24)	.28 (7)	1.18 (30)
CD21AS-EB2	.28 x .55 (7 x 14)					
CD29AS-EB1	.31 x .87 (8 x 22)	PG 29	1.47 (37.3)	1.14 (29)	.31 (8)	1.57 (40)
CD36AS-EB1	.39 x 1.12 (10 x 28.5)	PG 36	1.85 (47)	1.37 (35)	.31 (8)	1.97 (50)
CD36AS-EB2	.20 x 1.14 (5.5 x 29)					
CD36AS-EB3	.47 x 1.18 (12 x 30)					
CD36AS-EB4	.29 x 1.22 (7.5 x 31)					
CD42AS-EB1	.45 x 1.31 (11.5 x 33.5)	PG 42	2.13 (54.1)	1.46 (37)	.35 (9)	2.24 (57)
CD48AS-EB2	.47 x 1.50 (12 x 38)	PG 48	2.34 (59.4)	1.49 (38)	.39 (10)	2.52 (64)

ROMEX® is a federally registered trademark of Southwire Company.

Cable Glands with Inserts for Flat Cables

These form seals are also available with Cable Glands made of other materials. (Nickel Plated Brass, Stainless Steel, etc.)

* Additional UL Information

- Our FLAKA (for Romex® style cable) HSK-K-Ex PG 16 is UL listed (UL file # E168975)
- To meet UL, only Romex® style cable (flat top and bottom) can be used with this style Cable Glands (No Zip Cable, No Ribbon cable, etc.)
- Hummel Multi-hole solutions meet IP68 as long as the conductor outer diameter is not smaller than 20% of the hole diameter, or max 1 mm (.04") each. We recommend a customer performing his/her own testing.

