




For Non-Armored Cable

Nylon & Nickel Plated Brass, Cable Glands with Multi-Hole Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68

Part Numbers			Thread Type & Size	Dimensions in Inches (mm)			
-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)		No. of Holes	Diameter of Holes		Part Numbers of Inserts only
Black 	Gray 	Nickel Plated Brass 	mm		Inches		
CD07AP-BX	CD07AP-GX	CD07AP-MX	PG 7	Solid Insert		1.089.0799.19	
CD09A1-BX	CD09A1-GX	CD09A1-MX	PG 9	4	1.4	.06	1.089.0900.19
CD09A2-BX	CD09A2-GX	CD09A2-MX		2	3.0	.12	1.089.0901.19
CD09A3-BX	CD09A3-GX	CD09A3-MX		5	1.6	.06	1.089.0902.19
CD09A4-BX	CD09A4-GX	CD09A4-MX		2	1.7	.07	1.089.0903.19
CD09A5-BX	CD09A5-GX	CD09A5-MX		10	1.4	.06	1.089.0904.19
CD09A6-BX	CD09A6-GX	CD09A6-MX		6	1.4	.06	1.089.0905.19
CD09A7-BX	CD09A7-GX	CD09A7-MX		3	1.7	.07	1.089.0906.19
CD09A8-BX	CD09A8-GX	CD09A8-MX		4	1.7	.07	1.089.0907.19
CD09A9-BX	CD09A9-GX	CD09A9-MX		4	2.3	.09	1.089.0908.19
CD09AP-BX	CD09AP-GX	CD09AP-MX		Solid Insert		1.089.0999.19	
CD11A1-BX	CD11A1-GX	CD11A1-MX	PG 11	2	3.0	.12	1.089.1100.19
CD11A2-BX	CD11A2-GX	CD11A2-MX		3	3.0	.12	1.089.1101.19
CD11A3-BX	CD11A3-GX	CD11A3-MX		2	4.0	.16	1.089.1102.19
CD11A4-BX	CD11A4-GX	CD11A4-MX		3	1.5	.06	1.089.1103.19
CD11A5-BX	CD11A5-GX	CD11A5-MX		4	2.8	.11	1.089.1104.19
CD11AP-BX	CD11AP-GX	CD11AP-MX		Solid Insert		1.089.1199.19	
CD13A1-BX	CD13A1-GX	CD13A1-MX	PG 13 / 13.5	3	2.0	.08	1.089.1300.19
CD13A2-BX	CD13A2-GX	CD13A2-MX		6	3.0	.12	1.089.1301.19
CD13A3-BX	CD13A3-GX	CD13A3-MX		3	4.0	.16	1.089.1302.19
CD13A4-BX	CD13A4-GX	CD13A4-MX		2	5.0	.20	1.089.1303.19
CD13A5-BX	CD13A5-GX	CD13A5-MX		3	3.0	.12	1.089.1304.19
CD13A6-BX	CD13A6-GX	CD13A6-MX		2	5.2	.20	1.089.1305.19
CD13A7-BX	CD13A7-GX	CD13A7-MX		2	3.8	.15	1.089.1306.19
CD13A8-BX	CD13A8-GX	CD13A8-MX		2	4.2	.17	1.089.1307.19
CD13A9-BX	CD13A9-GX	CD13A9-MX		2	2.5	.10	1.089.1308.19
CD13AP-BX	CD13AP-GX	CD13AP-MX		Solid Insert		1.089.1399.19	
CD16A0-BX	CD16A0-GX	CD16A0-MX	PG 16	6	3.8	.15	1.089.1609.19
CD16A1-BX	CD16A1-GX	CD16A1-MX		3	3.0	.12	1.089.1600.19
CD16A2-BX	CD16A2-GX	CD16A2-MX		3	4.0	.16	1.089.1601.19
CD16A3-BX	CD16A3-GX	CD16A3-MX		4	4.0	.16	1.089.1602.19
CD16A4-BX	CD16A4-GX	CD16A4-MX		5	4.0	.16	1.089.1603.19
CD16A5-BX	CD16A5-GX	CD16A5-MX		6	4.0	.16	1.089.1604.19
CD16A6-BX	CD16A6-GX	CD16A6-MX		2	6.0	.24	1.089.1605.19
CD16A7-BX	CD16A7-GX	CD16A7-MX		3	5.6	.22	1.089.1606.19
CD16A8-BX	CD16A8-GX	CD16A8-MX		6	3.0	.12	1.089.1607.19
CD16A9-BX*	CD16A9-GX*	CD16A9-MX*		4	3.0	.12	1.089.1610.19*
CD16AP-BX	CD16AP-GX	CD16AP-MX		Solid Insert		1.089.1699.19	

\* Note: IECEx approval apply to only Nickel Plated Brass Multi-Hole

\*\*Note: UL F1 rating applies to Black Nylon Fittings only.

\* Note: This Insert has slotted holes.

\*\*\*Note: InMetro only applies to all Nylon Cable Glands.

For Specifications and Dimensions for Black Nylon (see page 18), Gray Nylon (see page 21) or Nickel Plated Brass (see page 33) where the appropriate Fittings are listed.



Additional Information

- Hummel Multi-hole solutions meet IP68 as long as the conductor outer diameter is not smaller than 20% of the hole diameter, or max 1 mm (.04") each. **We recommend a customer perform their own testing if IP68 rating needs to be achieved.**