


Technical Information



Material	Fibreglass reinforced polyamide V0 according to UL 94
Seal / O-Ring	NBR
Protection	IP 68 – 10 bar within the specified clamping range
Operating Temperature	- 20 °C – 85 °C (-4° F – 185° F)
Color	black



AG	∅ mm	 mm	H mm	GL mm	Number metr.	GL mm elongated	Number metr. elongated
M 12 x 1,5	3 – 6,5	15	21	8	1.292.1201.50	15	1.292.1201.30
M 12 x 1,5	2 – 5	15	21	8	1.292.1201.51	15	1.292.1201.31
M 16 x 1,5	4 – 8	19	22	8	1.292.1601.50	15	1.292.1601.30
M 16 x 1,5	3 – 6	19	22	8	1.292.1601.51	15	1.292.1601.31
M 16 x 1,5	5 – 10	22	25	8	1.292.1611.50	15	1.292.1611.30
M 16 x 1,5	3 – 7	22	25	8	1.292.1611.51	15	1.292.1611.31
M 20 x 1,5	6 – 12	24	27	9	1.292.2001.50	15	1.292.2001.30
M 20 x 1,5	5 – 9	24	27	9	1.292.2001.51	15	1.292.2001.31
M 20 x 1,5	10 – 14	27	28	9	1.292.2016.50	15	1.292.2016.30
M 20 x 1,5	7 – 12	27	28	9	1.292.2016.51	15	1.292.2016.31
M 25 x 1,5	13 – 18	33	31	11	1.292.2501.50	15	1.292.2501.30
M 25 x 1,5	9 – 16	33	31	11	1.292.2501.51	15	1.292.2501.31
M 32 x 1,5	18 – 25	42	39	11	1.292.3201.50	15	1.292.3201.30
M 32 x 1,5	13 – 20	42	39	11	1.292.3201.51	15	1.292.3201.31
M 40 x 1,5	22 – 32	53	48	13	1.292.4001.50	18	1.292.4001.30
M 40 x 1,5	20 – 26	53	48	13	1.292.4001.51	18	1.292.4001.31
M 50 x 1,5	32 – 38	60	49	13	1.292.5001.50	18	1.292.5001.30
M 50 x 1,5	25 – 31	60	49	13	1.292.5001.51	18	1.292.5001.31
M 63 x 1,5	37 – 44	65 / 68	49	14	1.292.6301.50	18	1.292.6301.30
M 63 x 1,5	29 – 35	65 / 68	49	14	1.292.6301.51	18	1.292.6301.31

NPT

NPT 3/8"	4 – 8	19 / 22	22	15	1.292.3801.70
NPT 3/8"	2 – 6	19 / 22	22	15	1.292.3801.71
NPT 1/2"	6 – 12	24	27	13	1.292.1201.70
NPT 1/2"	5 – 9	24	27	13	1.292.1201.71
NPT 1/2" (16)	10 – 14	27	28	13	1.292.1216.70
NPT 1/2" (16)	7 – 12	27	28	13	1.292.1216.71
NPT 3/4"	13 – 18	33	31	14	1.292.3401.70
NPT 3/4"	9 – 16	33	31	14	1.292.3401.71
NPT 1"	18 – 25	42	39	19	1.292.1001.70
NPT 1"	13 – 20	42	39	19	1.292.1001.71
NPT 1 1/4"	18 – 25	42 / 46	39	16	1.292.5401.70
NPT 1 1/4"	13 – 20	42 / 46	39	16	1.292.5401.71
NPT 1 1/2"	22 – 32	53	48	20	1.292.6401.70
NPT 1 1/2"	20 – 26	53	48	20	1.292.6401.71

7374 S. Eagle Street
Centennial, Colorado
80112-4221, U.S.A.
www.sealconex.com

PHONE: (303) 699-1135
FAX: (303) 680-5344

EMAIL: infoex@sealconex.com

SEALCON
Leading Provider of Cable Management Solutions