




For Non-Armored Cable

Nylon & Nickel Plated Brass, Cable Glands with Multi-Hole Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68

Part Numbers			Thread Type & Size	Dimensions in Inches (mm)				
-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)		No. of Holes	Diameter of Holes		Part Numbers of Inserts only	
Black	Gray	Nickel Plated Brass	mm		Inches			
			3/8" NPT  Page 55 for Thread Specs	4	1.4	.06	1.089.0900.19	
CD09N1-BX	CD09N1-GX	CD09N1-MX		2	3.0	.12	1.089.0901.19	
CD09N2-BX	CD09N2-GX	CD09N2-MX		5	1.6	.06	1.089.0902.19	
CD09N3-BX	CD09N3-GX	CD09N3-MX		2	1.7	.07	1.089.0903.19	
CD09N4-BX	CD09N4-GX	CD09N4-MX		10	1.4	.06	1.089.0904.19	
CD09N5-BX	CD09N5-GX	CD09N5-MX		6	1.4	.06	1.089.0905.19	
CD09N6-BX	CD09N6-GX	CD09N6-MX		3	1.7	.07	1.089.0906.19	
CD09N7-BX	CD09N7-GX	CD09N7-MX		4	1.7	.07	1.089.0907.19	
CD09N8-BX	CD09N8-GX	CD09N8-MX		4	2.3	.09	1.089.0908.19	
CD09N9-BX	CD09N9-GX	CD09N9-MX		Solid Insert			1.089.0999.19	
CD09NP-BX	CD09NP-GX	CD09NP-MX						
CD13N1-BX	CD13N1-GX	CD13N1-MX		1/2" NPT	3	2.0	.08	1.089.1300.19
CD13N2-BX	CD13N2-GX	CD13N2-MX			6	3.0	.12	1.089.1301.19
CD13N3-BX	CD13N3-GX	CD13N3-MX			3	4.0	.16	1.089.1302.19
CD13N4-BX	CD13N4-GX	CD13N4-MX			2	5.0	.20	1.089.1303.19
CD13N5-BX	CD13N5-GX	CD13N5-MX			3	3.0	.12	1.089.1304.19
CD13N6-BX	CD13N6-GX	CD13N6-MX	2		5.2	.20	1.089.1305.19	
CD13N7-BX	CD13N7-GX	CD13N7-MX	2		3.8	.15	1.089.1306.19	
CD13N8-BX	CD13N8-GX	CD13N8-MX	2		4.2	.17	1.089.1307.19	
CD13N9-BX	CD13N9-GX	CD13N9-MX	2		2.5	.10	1.089.1308.19	
CD13NP-BX	CD13NP-GX	CD13NP-MX	Solid Insert			1.089.1399.19		
CD16N0-BX	CD16N0-GX	CD16N0-MX	1/2"-E NPT	6	3.8	.15	1.089.1609.19	
CD16N1-BX	CD16N1-GX	CD16N1-MX		3	3.0	.12	1.089.1600.19	
CD16N2-BX	CD16N2-GX	CD16N2-MX		3	4.0	.16	1.089.1601.19	
CD16N3-BX	CD16N3-GX	CD16N3-MX		4	4.0	.16	1.089.1602.19	
CD16N4-BX	CD16N4-GX	CD16N4-MX		5	4.0	.16	1.089.1603.19	
CD16N5-BX	CD16N5-GX	CD16N5-MX		6	4.0	.16	1.089.1604.19	
CD16N6-BX	CD16N6-GX	CD16N6-MX		2	6.0	.24	1.089.1605.19	
CD16N7-BX	CD16N7-GX	CD16N7-MX		3	5.6	.22	1.089.1606.19	
CD16N8-BX	CD16N8-GX	CD16N8-MX		6	3.0	.12	1.089.1607.19	
CD16N9-BX*	CD16N9-GX*	CD16N9-MX*		4	3.0	.12	1.089.1610.19*	
CD16NP-BX	CD16NP-GX	CD16NP-MX	Solid Insert			1.089.1699.19		

\* Note: IECEx approval apply to only Nickel Plated Brass Multi-Hole  
 \*\*Note: UL f1 (746C) rating applies to Black Nylon Fittings only.  
 \* Note: This Insert has slotted holes.



For Specifications and Dimensions for Black & Gray Nylon (see page 19) or Nickel Plated Brass (see page 32) where the appropriate Fittings are listed.



Additional Information

- Hummel Multi-hole solutions meet IP68 as long as the conductor outer diameter is not smaller than 20% of the hole diameter, or max 1 mm (.04") each. **We recommend a customer perform their own testing if IP68 rating needs to be achieved.**

Ex-d EXIOS  
 Ex-d Nickel Plated Brass & Stainless Steel Glands  
 Nylon Glands  
 Ex-e Multi-Hole & Romex Glands  
 Ex-e Nickel Plated Brass & Stainless Steel Glands  
 Ex-e EMI / RFI Nickel Plated Brass Glands  
 Ex-e Conduit & Fitting Systems  
 Ex-e / Ex-d Accessories  
 Technical Information