

Ex-d EXIOS Cable Glands  
 Ex-d Nickel Plated Brass & Stainless Steel Glands  
 Ex-e Nylon Glands  
 Ex-e Multi-Hole & Romex Glands  
 Ex-e Nickel Plated Brass & Stainless Steel Glands  
 Ex-e EMI / RFI Nickel Plated Brass Glands  
 Ex-e Conduit & Fitting Systems  
 Ex-e / Ex-d Accessories  
 Technical Information

# Ex-e Nylon / Nickel Plated Brass - Multi-Hole Cable Glands - Metric Threads



## For Non-Armored Cable

Nylon & Nickel Plated Brass, Cable Glands with Multi-Hole Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68								
Part Numbers			Thread Type & Size	Dimensions in Inches (mm)			Part Numbers of Inserts only	
-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)	-4°F to 203°F (-20°C to 95°C)		No. of Holes	Diameter of Holes			
Black	Gray	Nickel Plated Brass	Page 55 for Thread Specs		mm	Inches		
				M25 x 1.5	4	6.0	.24	1.089.2100.19
CD25M1-BX	CD25M1-GX	CD25M1-MX	3		7.0	.28	1.089.2101.19	
CD25M2-BX	CD25M2-GX	CD25M2-MX	2		8.0	.31	1.089.2102.19	
CD25M3-BX	CD25M3-GX	CD25M3-MX	4		5.0	.20	1.089.2103.19	
CD25M4-BX	CD25M4-GX	CD25M4-MX	1		8.0	.31	1.089.2104.19	
CD25M5-BX	CD25M5-GX	CD25M5-MX	4		5.2	.20	1.089.2105.19	
CD25M6-BX	CD25M6-GX	CD25M6-MX	3		5.2	.20	1.089.2106.19	
CD25M7-BX	CD25M7-GX	CD25M7-MX	4/1		5.2/3.7	.20/.15	1.089.2107.19	
CD25M8-BX	CD25M8-GX	CD25M8-MX	2		7.4	.29	1.089.2108.19	
CD25M9-BX	CD25M9-GX	CD25M9-MX	Solid Insert			1.089.2199.19		
CD25MP-BX	CD25MP-GX	CD25MP-MX						
CD32M1-BX	CD32M1-GX	CD32M1-MX	M32 x 1.5		6	6.5	.26	1.089.2900.19
CD32M2-BX	CD32M2-GX	CD32M2-MX			4	9.0	.35	1.089.2901.19
CD32M3-BX	CD32M3-GX	CD32M3-MX		4	9.5	.37	1.089.2902.19	
CD32MP-BX	CD32MP-GX	CD32MP-MX		Solid Insert			1.089.2999.19	
CD40M1-BX	CD40M1-GX	CD40M1-MX	M40 x 1.5	5	9.0	.35	1.089.3600.19	
CD40M2-BX	CD40M2-GX	CD40M2-MX		7	9.0	.35	1.089.3601.19	
CD40M3-BX	CD40M3-GX	CD40M3-MX		6	8.0	.31	1.089.3602.19	
CD40M4-BX	CD40M4-GX	CD40M4-MX		2	15.0	.59	1.089.3603.19	
CD40MP-BX	CD40MP-GX	CD40MP-MX		Solid Insert			1.089.3699.19	
CD50M1-BX	CD50M1-GX	CD50M1-MX	M50 x 1.5	3	14.0	.55	1.089.4203.19	
CD50MP-BX	CD50MP-GX	CD50MP-MX		Solid Insert			1.089.4299.19	
CD63M1-BX	CD63M1-GX	CD63M1-MX	M63 x 1.5	8	10.0	.39	1.089.4800.19	
CD63M2-BX	CD63M2-GX	CD63M2-MX		6	12.0	.47	1.089.4801.19	
CD63M3-BX	CD63M3-GX	CD63M3-MX		3	18.0	.71	1.089.4802.19	
CD63MP-BX	CD63MP-GX	CD63MP-MX		Solid Insert			1.089.4899.19	

\* Note: IECEx approval apply to only Nickel Plated Brass Multi-Hole  
 \*\*Note: UL F1 rating applies to Black Nylon Fittings only.

\*\*\*Note: InMetro only applies to all Nylon Cable Glands.

For Specifications and Dimensions for Black Nylon (see page 17), Gray Nylon (see page 20) or Nickel Plated Brass (see page 32) where the appropriate Fittings are listed.



Elastomer Insert



Optional Locking Nuts & Other Accessories starting on page 43 - 51.

### Additional Information

- Hummel Multi-hole solutions meet IP68 as long as the conductor outer diameter is not smaller than 20% of the hole diameter, or max 1 mm (.04") each. **We recommend a customer perform their own testing if IP68 rating needs to be achieved.**

