


Thread Specifications

NPT Threads


Thread Size	3/8" NPT	1/2" NPT	3/4" NPT	1" NPT	1-1/4" NPT	1-1/2" NPT	2" NPT	3"
Major Dia. in Inches (mm)	.675 (17.145)	.84 (21.336)	1.05 (26.67)	1.314 (33.40)	1.66 (42.164)	1.90 (48.26)	2.375 (60.325)	3.50" (88.9)
Pitch in Inches (mm)	.056 (1.411)	.071 (1.814)	.071 (1.814)	.087 (2.208)	.087 (2.208)	.087 (2.208)	.087 (2.208)	.125" (3.175)
Number of Pitch n	18	14	14	11 1/2	11 1/2	11 1/2	11 1/2	8



- NPT Thread = National Pipe Thread
- Taper rate for all NPT threads is 1/16
- The taper on NPT threads allows them to form a seal when torqued as the flanks of the threads compress against each other, as opposed to straight thread fittings

Metric Threads


Thread Size	M12	M16	M20	M25	M32	M40	M50	M63	M75	M90
Major Dia. in Inches (mm)	.47 (12)	.63 (16)	.79 (20)	.98 (25)	1.26 (32)	1.57 (40)	1.97 (50)	2.48 (63)	2.36" (60)	2.95" (75)
Pitch in Inches (mm)	.059 (1.5)	.059 (1.5)	.059 (1.5)	.059 (1.5)	.059 (1.5)	.059 (1.5)	.059 (1.5)	.059 (1.5)	.059" (1.5)	.79" (2.0)
Thru hole in inches (mm)	.492 (12.5)	.63 (16)	.79 (20)	.98 (25)	1.26 (32)	1.57 (40)	1.97 (50)	2.48 (63)	2.36" (60)	2.95" (75)



- Most commonly used thread type world-wide
- Characterized by its major diameter and its pitch
- Designated by the letter M followed by the value of the nominal diameter and the pitch, both expressed in millimeters and separated by the multiplication sign 'x' (i.e. M12 x 1.5)

PG Threads

Thread Size	PG 7	PG 9	PG 11	PG 13 / 13.5	PG 16	PG 21	PG 29	PG 36	PG 42	PG 48
Major Dia. in Inches (mm)	.49 (12.5)	.60 (15.2)	.73 (18.6)	.80 (20.4)	.89 (22.5)	1.11 (28.3)	1.46 (37)	1.85 (47)	2.13 (54)	2.39 (59.3)
Pitch in Inches (mm)	.05 (1.27)	.055 (1.41)	.055 (1.51)	.055 (1.51)	.055 (1.51)	.062 (1.59)	.062 (1.59)	.062 (1.59)	.062 (1.59)	.062 (1.59)
Thru hole in inches (mm)	.50 (12.7)	.606 (15.4)	.74 (18.8)	.8149 (20.7)	.897 (22.8)	1.12 (28.6)	1.47 (37.4)	1.87 (47.5)	2.14 (54.5)	2.35 (59.8)



- PG Thread = Panzer-Gewinde (Panzer-Rohr-Gewinde)
- German thread type
- Depth of thread smaller than NPT or Metric, but larger flank angle

**Other Technical Information
 can be found online at
www.sealconex.com**

For questions please call our Inside Technical Sales Department - 1-800-456-9012 or 303-699-1135.

Ex-d EXIOS Cable Glands
 Ex-d Nickel Plated Brass & Stainless Steel Glands
 Nylon Glands
 Ex-d Multi-Hole & Romex Glands
 Ex-d Nickel Plated Brass & Stainless Steel Glands
 Ex-d FMI / RFI Nickel Plated Brass Glands
 Ex-d Conduit & Fitting Systems
 Accessories
 Technical Information