

Sealcon Part Numbers	Hummel Part Numbers	Hummel Description	Sealcon Page Nr.
CDxxNx-MX	1.687	HSK-M-Multi-Ex	28-29
DUOxxMx-MX	1.566	Snapclip-DUO-MX	45
HM-xx-6IX-D	1.897	V-INOX-Ex-d (Silicon)	50
HM-xx-6VX-D	1.896	V-INOX-Ex-d (Viton)	50
HM-xx-6X-D	1.895	V-INOX-Ex-d (Buna-N)	50
HM-xx-BX	1.297	V-Ex	49
HM-xx-MIX-D	1.896	V-INOX-Ex-d (Silicone)	50
HM-xx-MX-D	1.895	V-INOX-Ex-d (Buna-N)	50
HM-xx-MX-S	1.199	V-Ms-Ex (Silicone)	49
HM-xx-MX-V	1.198	V-Ms-Ex (Viton)	49
HM-xx-MVX-D	1.897	V-INOX-Ex-d (Viton)	50
HM-xx-SX	1.192	V-INOX-Ex	50
HM-xx-SX-S	1.193	V-INOX-VMQ-Ex	50
HM-xx-SX-V	1.194	V-INOX-FPM-Ex	50
HP-xx-BX	1.297	V-Ex	49
HP-xx-MX	1.197	V-Ms-Ex	49
HP-xx-MX-S	1.199	V-Ms-VMQ-Ex	49
HP-xx-MX-V	1.198	V-Ms-FPM-Ex	49
HP-xx-SX	1.192	V-INOX-Ex	50
HP-xx-SX-S	1.193	V-Ms-VMQ-Ex	50
HP-xx-SX-V	1.194	V-INOX-FPM-Ex	50
MC-xx-BX	1.731	Snapclip-Ex	45
NM-xx-BE	1.167	GM-EMV	47
NM-xx-BK	1.262	GM-FS	48
NM-xx-BR	1.161	GM-Ms	47
NM-xx-GY	1.262	GM-FS	48
NM-xx-SS	1.161	GM-INOX	46
NM-xx-XL	1.161	GM-Ms	47
NN-xx-BE	-	GM-EMV	47
NN-xx-BK	-	GM-FS	48
NN-xx-BR	-	GM-Ms	47
NN-xx-GY	-	GM-FS	48

Sealcon Part Numbers	Hummel Part Numbers	Hummel Description	Sealcon Page Nr.
NN-xx-ST	-	-	47
NP-xx-BE	1.167	GM-EMV	47
NP-xx-BK	1.262	GM-FS	48
NP-xx-BR	1.161	GM-Ms	47
NP-xx-GY	1.262	GM-FS	48
NP-xx-SS	1.161	GM-INOX	46
PV-xx-BX	1.296	HSK-V-Ex	48
RM-xxxx-6X-D	1.898	RSD-INOX-Ex-d	53
RM-xxxx-6IX-D	1.899	RSD-INOX-Ex-d-VMQ	53
RM-xxxx-MX	1.078	RSD-Ms-Ex	51
RM-xxxx-MX-D	1.878	RSD-Ms-Ex-d	53
RM-xxxx-MIX-D	1.879	RSD-Ms-Ex-d-VMQ	53
RM-xxxx-MX-S	1.079	RSD-Ms-VMQ-Ex	51
RM-xxxx-SX	1.098	RSD-INOX-Ex	52
RM-xxxx-SX-S	1.099	RSD-INOX-VMQ-Ex	52
RQ-xxxx-MX	1.078	RSD-Ms-Ex	51
RQ-xxxx-MX-S	1.079	RSD-Ms-VMQ-Ex	51
RQ-xxxx-SX	1.098	RSD-INOX-Ex	52
RQ-xxxx-SX-S	1.099	RSD-INOX-VMQ-Ex	52
SE-xx-PV	1.802	-	54
SF-xxxx-BX	1.560	Snapflex-Ex	45
SM-, SR-xx-FN	1.326	Red Fiber Washer	54
TN-, TM-xx-BB, -BR	1.022	Earhtag	54
WN-, WM-xx-SS	1.329	Serrated Washer	54
YAx-xx-BB	1.608	EXIOS A2F	12
YEx-xx-BB, B1	1.605	EXIOS Standard	8
YP-xx-BB, B1	1.606	EXIOS Barrier	6
YU-xx-B1, BR	1.6U6	EXIOS UL Barrier	4
YZ-xx-BB, B1	1.605	EXIOS MZ	9

## Sealcon - Hazloc Solutions Qualifying Questions & Inquiry Form

**Ratings & Approvals:**

- Ex-i
- Ex-e
- Ex-d
- ATEX
- IECEX
- UL
- CSA (cUS)
- Other : \_\_\_\_\_

**Euro Zone:**

- 0  1  2 (Gas)
- 20  21  22 (Dust)

**Class & Div**

- Class 1 Div 1 (Gas)
- Class 1 Div 2 (Gas)
- Class 2 Div 1 (Dust)
- Class 2 Div 2 (Dust)

**Gland / SRF Material:**

- Brass
- Nickel Plated
- 316 Stainless Steel
- Nylon / Plastic
- Snapflex / DUOFitting
- Circular Connectors
- Other: \_\_\_\_\_

**Operating Temp:**

- 60°C to 105°C (EXIOS)
- 20°C to 95°C (SRF)
- 20°C to 130°C (PVDF)
- Other: \_\_\_\_\_

**IP Ratings:**

- 66  67
- 68  Other: \_\_\_\_

**Cable Types:**

- SWA (Steel Wire Armor) W
- SWB (Steel Wire Braid) X
- DST (Double-Steel Tape) Z
- (Lead Sheath)
- (Unarmored)
- (Tek/MC/Corrugated)

**Armor thickness:**

- 0 - 2.5 mm (up to 0.1")

**Compound Filled:**

- Yes  No

**Thread:**

- METRIC
- NPT
- Other: \_\_\_\_\_

**Sizes):**

- Metric: M12, M16, M20, M25, M32, M40, M50, M63, M75

**NPT:**

- 3/8", 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3"

**Accessories:**

- Shrouds
- Serrated Washers
- Earth Tags
- Red Fiber Washer
- Lock Nuts
- Hex Plugs
- Blind Plugs
- Adapters
- Reducers
- Breather Drain

<b>Cable Description:</b>	<b>Cable I.D. – O.D.:</b>	<b>Gland Quantity:</b>
---------------------------	---------------------------	------------------------

<b>Requesting:</b>				
<input type="checkbox"/> Sample	<input type="checkbox"/> Quote	<input type="checkbox"/> Catalog	<input type="checkbox"/> Certifications	<input type="checkbox"/> Other

Ex-d EXIOS Cable Glands  
 Ex-d Nickel Plated Brass & Stainless Steel Glands  
 Ex-e Nylon Glands  
 Ex-e Multi-Hole & Romex Glands  
 Ex-e Nickel Plated Brass & Romex Glands  
 Ex-e EMI / RFI Nickel Plated Brass Glands  
 Ex-e Conduit & Fitting Systems  
 Ex-e / Ex-d Accessories  
 Technical Information