Ex-e Nylon Glands

Nickel Plated Brass & Stainless Steel Cable Glands Features & Benefits - Ex-e



Ref. Standards

EN 60079-0

EN 60079-7

E103997

104031

0 UE11

UL/UR

CSA

CAGE

For Non-Armored Cable

Technical Description

- Ex-e Cable Glands for non-armored cable Cost Saving Option!
- Approvals & Certifications ATEX/IECEx, UL/UR, CE, CSA, Gost and German Lloyd!
- NEMA 4x & 6 (IP 67 & 68) Liquid Tight Submersible to 300 ft!
- IP 69K rated Ideal in splash or hose down applications!
- Patented form seal allows 150 PSIG (10 BAR) rating Highest in Industry!
- V0 flame rating according to UL 94 Halogen & Phosphorous Free non toxic!
- RoHS & Deca BDE Environmentally Compliant to the newest standards!
- Large selection in Nickel Plated Brass and Stainless Steel Cable Range from .08" (2 mm) to 1.73" (44 mm)
- Non-Corrosive Resistant to salt water, weak acids, weak alkalis, alcohol, esters, ketones, ether, gasoline, mineral, animal & vegetable oil.

Your One Stop Solution For All Cable & Wire Accessories!



Unique Product

The patented recess form seal guarantees NEMA 4x & 6 (IP 68 / IP 69K) at 150 PSIG (10 BAR).

Pull-out Resistance & Cable Protection

Overlapping clamping splines apply a concentric force, preventing the form seal from being pulled out of the gland. This ensures pull-out protection without damage to the cable.

Liquid Tight

Machined O-Ring Groove: All of our Ex Cable Glands come with an O-Ring, resulting in a Liquid Tight Seal between cable gland and installation.

Time Saving Installation

Simply push the cable through Cable Glands - Tighten Dome Nut - Done! No disassembly of the cable glands required!





