

CERTIFICATE OF COMPLIANCE

Certificate Number 20140312-E351373
Report Reference E351373-20140311
Issue Date 2014-MARCH-12

Issued to: HUMMEL AG
LISE-MEITNER-STRASSE 2
DENZLINGEN, 79211 GERMANY

**This is to certify that
representative samples of**


MARINE SHIPBOARD CABLE SEALING FITTINGS FOR
USE IN HAZARDOUS LOCATIONS;
MARINE SHIPBOARD CABLE FITTINGS FOR USE IN
ZONE CLASSIFIED HAZARDOUS LOCATIONS
See addendum page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 2225, Cables, and Cable-Fittings for Use in Hazardous
(Classified) Locations;
UL 514B, Conduit, Tubing and Cable Fittings;
CSA C22.2 No. 174-M1984, Cable, and Cable Glands for
Use in Hazardous Locations;
CSA C22.2 No. 18.3, Conduit, Tubing, and Cable Fittings

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as
being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US
and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and
"US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL;
and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140312-E351373
Report Reference E351373-20140311
Issue Date 2014-MARCH-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL - Marine Shipboard Cable Sealing Fittings. For use in Class I, Groups C and D; Class II, Groups E, F, and G; Class III Hazardous Locations. For use with armored braided marine shipboard cable employing aluminum, bronze, copper, or stainless steel bonding braid and Polymeric Systems Inc. Kneadaseal sealing compound. Thread sizes 1/2 to 3 in. NPT inclusive or M20 to M75 inclusive, for vertical or horizontal mounting.


Models EXIOS Barrier 20-1, EXIOS Barrier 20-2, EXIOS Barrier 20-3, EXIOS Barrier 25, EXIOS Barrier 32, EXIOS Barrier 40, EXIOS Barrier 50, EXIOS Barrier 63, and EXIOS Barrier 75

USL, CNL – Marine Shipboard Cable Sealing Fittings. For use in Class I, Division 2, Groups C, and D; Class II, Groups F and G; Class III Hazardous Locations. For use with unarmored marine shipboard cable and Polymeric Systems Inc. Kneadaseal sealing compound. Thread sizes 1/2 to 3 in. NPT inclusive or M20 to M75 inclusive, for vertical or horizontal mounting.

Models EXIOS Barrier 20-1, EXIOS Barrier 20-2, EXIOS Barrier 20-3, EXIOS Barrier 25, EXIOS Barrier 32, EXIOS Barrier 40, EXIOS Barrier 50, EXIOS Barrier 63, and EXIOS Barrier 75

USL - Marine Shipboard Cable Sealing Fittings. For use in Class I, Zone 1, AEx d IIB Hazardous Locations. For use with armored braided marine shipboard cable employing aluminum, bronze, copper, or stainless steel bonding braid and Polymeric Systems Inc. Kneadaseal sealing compound. Thread sizes 1/2 to 3 in. NPT inclusive or M20 to M75 inclusive, for vertical or horizontal mounting.

Models EXIOS Barrier 20-1, EXIOS Barrier 20-2, EXIOS Barrier 20-3, EXIOS Barrier 25, EXIOS Barrier 32, EXIOS Barrier 40, EXIOS Barrier 50, EXIOS Barrier 63, and EXIOS Barrier 75



William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

